


## VERIFICATION OF TRANSLATION

---

Re: Japanese Patent Application No. 2004-149583

I, Tsuyoshi Kumano of 1-50, Hagiharadai-nishi,  
Kawanishi-shi, Hyogo-ken, Japan, hereby declare  
that I am the translator of the documents attached  
and certify that the following is a true translation  
to the best of my knowledge and belief.

Signature of translator



.....

Dated this 18th June 2010

Japanese Patent Application No. 2004-149583

[Name of document]	Patent Application
[Reference number]	P16-187
[Filing date]	May 19, 2004
[Addressee]	Commissioner of the Patent
Office	
[IPC]	F16C 35/02
[Inventor]	
[Address or residence]	c/o NTN Corporation, 3066, Aza
Oyumida,	
	Oaza Higashikata, Kuwana-shi,
Mie Japan	
[Name]	Katsuo Shibahara
[Inventor]	
[Address or residence]	c/o NTN Corporation, 3066, Aza
Oyumida,	
	Oaza Higashikata, Kuwana-shi,
Mie Japan	
[Name]	Isao Komori
[Patent applicant]	
[Identification number]	000102692
[Name]	NTN Corporation
[Agent]	
[Identification number]	100064584
[Patent attorney]	
[Name]	Syogo Ehara
[Appointed agent]	
[Identification number]	100093997
[Patent attorney]	
[Name]	Hideyoshi Tanaka
[Appointed agent]	
[Identification number]	100101616
[Patent attorney]	
[Name]	Yoshiyuki Shiraishi

[Appointed agent]  
 [Identification number] 100107423  
 [Patent attorney]  
 [Name] Kunihiro Shiromura  
 [Appointed agent]  
 [Identification number] 100120949  
 [Patent attorney]  
 [Name] Tsuyoshi Kumano  
 [Phone number ] 06-6443-9541  
 [Contact name ] same as above  
 [Appointed agent]  
 [Identification number] 100121186  
 [Patent attorney]  
 [Name] Hiroaki Yamane  
 [FEE]  
 [Deposit account number] 019677  
 [Amount] ¥16,000  
 [List of materials presented]  

[Name of material]	Claims	1
[Name of material]	Specification	1
[Name of material]	Drawings	1
[Name of material]	Abstract	1

[Claims]

1. A dynamic pressure bearing device comprising:  
a shaft member having a shaft portion and a flange portion;  
and  
a thrust bearing portion for generating a pressure by a dynamic pressure effect of a fluid in a thrust bearing gap between an end face of the flange portion and a face being opposed thereto so as to support the shaft member in an axial direction in a non-contact manner by the pressure, wherein  
the end face of the flange portion facing the thrust bearing gap is formed of a resin and at least a part of the end face facing the thrust bearing gap is formed as an inclined plane coming closer to an opposed face in a radially outward direction.
2. The dynamic pressure bearing device according to claim 1, wherein a radially inner side of the end face of the flange portion, which faces the thrust bearing gap, is made of a thick resin and a radially outer side thereof is made of a thinner resin than the thick resin.
3. The dynamic pressure bearing device according to claim 1, wherein the shaft member includes: an outer shaft portion forming an outer peripheral face of the shaft portion; and an inner shaft portion provided on an inner periphery of the outer shaft portion,  
the outer shaft portion is formed of a metal, and  
the inner shaft portion and the flange portion are integrally formed of a resin.
4. The dynamic pressure bearing device according to claim 3, wherein an angle  $\theta$  of inclination of the inclined plane is set to  $\theta \leq 0.6^\circ$ .
5. A motor having: the dynamic pressure bearing device

according to any one of claims 1 to 4, a rotor magnet; and a stator coil.

[Name of document] Specification

[Title of invention] DYNAMIC PRESSURE BEARING DEVICE

[Detailed description of the invention]

[Technical field of the invention]

[0001]

The present invention relates to a dynamic pressure bearing device. This bearing device is suitable for: a spindle motor for information equipment, for example, a magnetic disk device such as an HDD or an FDD, an optical disk device for a CD-ROM, a DVD-ROM or the like, and a magneto-optical disk device for an MD, an MO or the like; a polygon scanner motor for a laser beam printer (LBP); and a small motor for electric equipment, for example, an axial fan and the like.

[Background Art]

[0002]

The above-mentioned various motors are required to operate not only with high rotational accuracy but also at higher speed, lower cost, and lower noise. One of the components determining the required performance is a bearing for supporting a spindle of the motor. As this type of bearing, a dynamic pressure bearing device having characteristics excellent in the above-mentioned required performance has been considered for use or has been put into practical use in recent years.

[0003]

As an example of the dynamic pressure bearing device, Japanese Patent Laid-Open Publication No. 2002-61641 discloses a dynamic pressure bearing device having the following structure. The dynamic pressure bearing device includes: a cylindrical housing with a closed end; a bearing member fixed to an inner periphery of the housing; a shaft member inserted onto an inner peripheral face of the bearing member; and a radial bearing portion and a thrust bearing portion, which rotatably support the shaft member in a non-contact manner by a dynamic pressure effect generated during the relative rotation of the shaft member and a bearing sleeve.

[0004]

Of the radial bearing portion and the thrust bearing portion, the thrust bearing portion generates a pressure by a dynamic pressure effect of oil in each of thrust bearing gaps between both end faces of a flange of the shaft member and a bottom face of the housing and an end face of the bearing sleeve, which are opposed thereto, so as to support the shaft member in an axial direction in a non-contact manner.

[Prior art document] JP2002-61641A1

[Disclosure of invention]

[Problems to be solved by the invention]

[0005]

In this type of dynamic pressure bearing device, a member on the rotational side and a member on the fixed side inevitably slide with each other at high speed when the dynamic pressure bearing device starts and stops operating. Therefore, in the dynamic pressure bearing device used for information equipment in which the operation of a motor is frequently started and stopped, for example, consumer equipment including an HDD-DVD recorder and a storage device for a cell-phone, the wear of a sliding face caused by repeated start and stop of the operation emerges as a problem under some conditions for use and the like. Thus, wear resistance is desired to be further improved. In particular, in the case where the flange is made of a resin, wear is more likely to be accelerated as compared with the case where metals slide with each other. Accordingly, there is a possibility that bearing performance may be degraded within a short period of time due to the effect of abrasion powder.

[0006]

In view of the above problems, the present invention has an object of providing a dynamic pressure bearing device capable of preventing wear of a thrust bearing portion.

[Means for solving the problems]

[0007]

In order to achieve the above object, a dynamic bearing device according to the present invention comprises: a shaft

member having a shaft portion and a flange portion; and a thrust bearing portion for generating a pressure by a dynamic pressure effect of a fluid in a thrust bearing gap between an end face of the flange portion and a face being opposed thereto so as to support the shaft member in an axial direction in a non-contact manner by the pressure, wherein the end face of the flange portion facing the thrust bearing gap is formed of a resin and at least a part of the end face facing the thrust bearing gap is formed as an inclined plane coming closer to an opposed face in a radially outward direction.

[0008]

As a result, the radially outermost portion of the part of the end face of the flange portion, which faces the thrust bearing gap, has the minimum width of the thrust bearing gap. The highest peripheral speed can be obtained at this portion in the thrust bearing gap. Since the pumping power by dynamic pressure generating means such as dynamic pressure generating grooves is enhanced in this minimum width portion in this case, contact time between the thrust bearing surface and the thrust receiving surface at the start or the stop of operation of the motor can be reduced. As a result, wear of the thrust bearing portion can be prevented. The inclined plane may be formed not only as a flat tapered surface but also as a curved face.

[0009]

The inclined plane on the end face of the flange portion may be formed by making use of a level difference of a sink generated when a resin part of the shaft member is hardened. For example, if a radially inner side of the end face of the flange portion, which faces the thrust bearing gap, is made of a thick resin while a radially outer side thereof is made of a thinner (a difference between thick and thin is defined by an axial thickness) resin than the thick resin, an amount of sink in the axial direction becomes large on the radially inner side as compared with that on the radially outer side when the resin is hardened. Therefore, the inclined plane can be provided on the end face of the flange portion by making use



of a difference in the amount of sink.

[0010]

The shaft member includes: an outer shaft portion forming an outer peripheral face of the shaft portion; and an inner shaft portion provided on an inner periphery of the outer shaft portion, the outer shaft portion is formed of a metal, and the inner shaft portion and the flange portion are integrally formed of a resin. With such a structure, the radially inner side of the flange portion is made of a resin having a larger thickness than that of the radially outer side by the presence of the inner shaft portion. Therefore, a difference is generated in the amount of sink between on the radially inner side and on the radially outer side of the flange portion. As a result, the inclined plane can be formed on the end face of the flange portion.

[0011]

It is desirable to set an angle  $\theta$  of inclination of the inclined plane such that  $\theta \leq 0.6^\circ$ , preferably  $\theta \leq 0.3^\circ$ . It is found by the inventor that the contact start rotational speed becomes excessive thereby causes the decrease of the dynamic pressure effect, if the angle  $\theta$  of inclination exceeds the upper limit.

[0012]

A motor including: the above-described dynamic pressure bearing device; a rotor magnet; and a stator coil has high durability as well as high rotational accuracy. Therefore, the motor is suitable as a motor for information equipment.

[Effects of the invention]

[0013]

According to the invention, since wear of the thrust bearing portion can be prevented according to the present invention, the durability of the dynamic pressure bearing device can be improved.

[Best mode for carrying out the invention]

[0014]

Hereinafter, embodiments of the present invention will

be described.

[0015]

Fig. 2 shows a spindle motor used for a disk drive device such as an HDD as an example of a spindle motor for information equipment incorporating a dynamic pressure bearing device 1. The motor includes: the dynamic pressure bearing device 1; a rotational member 3 (a disk hub) attached to a shaft member 2 of the dynamic pressure bearing device 1; a stator coil 4 and a rotor magnet 5 provided so as to be opposed to each other, for example, through a radial gap; and a bracket 6. The stator coil 4 is attached to an outer periphery of the bracket 6. The rotor magnet 5 is attached to an inner periphery of the disk hub 3. The disk hub 3 retains one or a plurality of disks D such as a magnetic disk on its outer periphery. A housing 7 of the dynamic pressure bearing device 1 is attached to an inner periphery of the bracket 6. When the stator coil 4 is energized, the rotor magnet 5 is rotated by an excitation force generated between the stator coil 4 and the rotor magnet 5. With the rotation of the rotator magnet 5, the disk hub 3 rotates, which in turn rotates the shaft member 2.

[0016]

Fig. 3 shows an example of the dynamic pressure bearing device 1 described above. The dynamic pressure bearing device 1 includes: radial bearing portions R1 and R2 for supporting the shaft member 2 in a radial direction; and thrust bearing portions T1 and T2 for supporting the shaft member 2 in an axial direction. Each of the radial bearing portions R1 and R2 and the thrust bearing portions T1 and T2 is constituted by a dynamic pressure bearing. The dynamic pressure bearing forms a bearing surface including dynamic pressure generating grooves on any one of a rotational-side member and a fixed-side member while forming a smooth receiving surface on the other member so as to be opposed to the bearing surface. During rotation of the rotational-side member, a pressure is generated by a dynamic pressure effect of a fluid in a bearing gap between the bearing surface and the receiving surface to rotatably support the

rotational-side member in a non-contact manner.

[0017]

Hereinafter, a specific structure of the dynamic pressure bearing device 1 will be described.

[0018]

As shown in Fig. 3, the dynamic pressure bearing device 1 according to this embodiment includes as principle bearing components: the cylindrical housing 7 having a closed end and an opening 7a on the other end; a cylindrical bearing sleeve 8 fixed onto an inner peripheral face of the housing 7; the shaft member 2; and a sealing member 10 fixed into the opening 7a of the housing 7. For convenience of description, the opening side of the housing 7 is referred to as an upper side while the opposite side in the axial direction is referred to as a lower side in the following description.

[0019]

The housing 7 is formed in a cylindrical shape with a closed end, including a cylindrical side portion 7b and a bottom portion 7c. In this embodiment, the bottom portion 7c is formed by a disc-like thin thrust plate as a member independent of the side portion 7b. The thrust plate 7c is bonded to and/or pressed into a lower opening of the side portion 7b so as to be attached thereto, thereby forming the housing 7 having a closed end. The bottom portion 7c of the housing 7 may be integrally formed with the side portion 7b. The side portion 7b and the bottom portion 7c of the housing 7 may be formed of any one of a metal material and a resin material.

[0020]

The shaft member 2 has, as described below, a composite structure made of a resin and a metal. The shaft member 2 includes: a shaft portion 2a; and a flange portion 2b provided on a lower end of the shaft portion 2a so as to be extended in a radially outward direction. A lower end face 2b1 of the flange portion 2b is opposed to an upper end face 7c1 of the thrust plate 7c, whereas an upper end face 2b2 of the flange portion 2b is opposed to a lower end face 8c of the bearing sleeve 8.

[0021]

In this embodiment, a part of the upper end face 7c1 of the thrust plate 7c, which is opposed to the lower end face 2b1 of the flange portion 2b, serves as the thrust bearing surface 11a of the lower thrust bearing portion T1. On a part of the thrust bearing surface 11a, for example, in the vicinity of the radial center of the thrust bearing surface 11a, a dynamic pressure generating groove area P is annularly formed as shown in Fig. 3. The dynamic pressure generating groove area P is formed by spirally arranging a plurality of dynamic pressure generating grooves P1 and a plurality of ridges P2, each forming a like-hill between the dynamic pressure generating grooves P1. A pattern of the dynamic pressure generating grooves in the dynamic pressure generating groove area P is arbitrary and can be arranged in a herringbone pattern.

[0022]

The bearing sleeve 8 is formed of an oil-impregnated sintered metal in a cylindrical shape. The oil-impregnated sintered metal is obtained by impregnating, for example, a porous material, in particular, a sintered metal on the basis of copper into a lubricating oil (or a lubricating grease). A radial bearing surface of the first radial bearing portion R1 and a radial bearing surface of the second radial bearing portion R2 are provided on an inner peripheral face 8a of the bearing sleeve 8 so as to be axially separated from each other. Dynamic pressure generating grooves in, for example, a herringbone pattern are formed in each of the two areas. A spiral pattern, an axial groove pattern or the like may be used as a pattern of the dynamic pressure generating grooves. The radial bearing surfaces including the dynamic pressure generating grooves may also be formed on an outer peripheral face of the shaft portion 2a of the shaft member 2. Furthermore, the bearing sleeve 8 may be formed of a material other than the porous material, for example, a soft metal such as brass or a copper alloy. An annular dynamic pressure generating groove area (not shown) where a plurality of dynamic pressure

generating grooves are spirally arranged is formed on the lower end face 8c of the bearing sleeve 8.

[0023]

As shown in Fig. 3, the sealing member 10 is annular and is fixed into an inner peripheral face of the opening 7a of the housing 7 by means such as pressing or bonding. In this embodiment, an inner peripheral face 10a of the sealing member 10 is formed in a cylindrical shape, and a lower end face of the sealing member 10 abuts against the upper end face 8b of the bearing sleeve 8.

[0024]

The shaft portion 2a of the shaft member 2 is inserted onto the inner peripheral face 8a of the bearing sleeve 8. The flange portion 2b is housed in a space between the lower end face 8c of the bearing sleeve 8 and the upper end face 7c1 of the thrust plate 7c. A tapered surface 2a of the shaft portion 2a is opposed to the inner peripheral face 10a of the sealing member 10 with a predetermined gap therebetween. As a result, a tapered sealed space S that gradually expands in the outer direction of the housing 7 (upwardly in the drawing) is formed between the tapered surface 2a and the inner peripheral face 10a. During the rotation of the shaft member 2, the tapered surface 2a1 of the shaft portion 2a also serves as a so-called centrifugal seal. An internal space in the housing 7 (including pores in the bearing sleeve 8) sealed by the sealing member 10 is filled with a lubricating oil. An oil level of the lubricating oil is present in the sealed space S. The sealed space S is formed not only in a tapered shape as described above but also in a cylindrical shape having the same diameter in the axial direction.

[0025]

In the above-described embodiment, when the shaft member 2 is rotated by motor rotation, a pressure is generated by a dynamic pressure effect of the lubricating oil in a radial bearing gap between the radial bearing surface on the inner peripheral face of the bearing sleeve 8 and the outer peripheral

face of the shaft portion 2a (the radial receiving surface) being opposed thereto in the radial bearing portions R1 and R2. As a result, the shaft portion 2a of the shaft member 2 is supported so as to be rotatable in the radial direction in a non-contact manner. Moreover, in the lower thrust bearing portion T1, a pressure is generated by a dynamic pressure effect of the lubricating oil in the thrust bearing gap between the dynamic pressure generating groove area P formed on the upper end face 7c1 (the thrust bearing surface 11a) of the thrust plate 7c and the lower end face 2b1 (the thrust receiving surface 11b) of the flange portion 2b being opposed thereto. At the same time, in the upper thrust bearing portion T2, a pressure is generated by a dynamic pressure effect of the lubricating oil in a thrust bearing gap between the dynamic pressure generating groove area (not shown) formed on the lower end face 8c (the thrust bearing surface 13a) of the bearing sleeve 8 and the upper end face 2b2 (the thrust receiving surface 13b) of the flange portion 2b being opposed thereto. Therefore, the flange portion 2b of the shaft member 2 is supported so as to be rotatable in the axial direction in a non-contact manner.

[0026]

Although the dynamic pressure generating groove area P are formed on the upper end face 7c1 of the thrust plate 7c and the lower end face 8c of the bearing sleeve 8, respectively, the dynamic pressure generating groove area P may also be formed on any one of or both of the end faces 2b1 and 2b2 of the flange portion 2b. In this case, the upper end face 7c1 of the thrust plate 7c or the lower end face 8c of the bearing sleeve 8 is served as the thrust receiving surface without a dynamic pressure generating groove.

[0027]

As shown in Fig. 1, the shaft member 2 has a composite structure made of a resin and a metal. The resin part includes an inner shaft portion 22 extending in the axial direction and the flange portion 2b extending in the radially outward direction from the inner shaft portion 22, which are integrally

formed. An outer shaft portion 22 covering the outer periphery of the inner shaft portion 22 is made of a metal material, for example, stainless steel excellent in wear resistance in a cylindrical hollow shape. It is possible to use PEEK, PPS, LCP, 9T nylon or the like as a resin material. A filler such as a glass fiber, a carbon fiber or an electric conducting agent is blended with the above-described base resin above as needed. In the case where the carbon fiber is used, in particular, it is preferred to blend a PAN carbon fiber having a mean fiber diameter of 1 to 12  $\mu\text{m}$  and a mean fiber length of 100 to 500  $\mu\text{m}$  at a blending rate of 5 to 30 vol% with the base resin.

[0028]

In order to prevent the outer shaft portion 21 made of the metal material and the inner shaft portion 22 and the flange portion 2b made of the resin material from being separated from each other, an end portion 21a is embedded into the flange portion 2b at the lower end of the outer shaft portion 21, whereas an upper end of the outer shaft portion 21 is engaged with the inner shaft portion 22 in the axial direction through, for example, an engaging portion formed by a tapered plane or the like. It is desirable to provide convex and concave portions, which are engageable with the inner shaft portion 22 or the flange portion 2b in the peripheral direction, on the inner peripheral face of the outer shaft portion 21 or the outer peripheral face of the outer shaft portion 21 embedded into the flange portion 2b so that the outer shaft portion 21 does not rotate.

[0029]

In the present invention, as shown in an enlarged manner in Fig. 1, the curved inclined plane 17 coming closer to an opposed face (the upper end face 7c1 of the thrust plate 7c in this embodiment) in the radially outward direction is provided on the lower end face 2b1 of the flange portion 2b. By forming the inclined plane 17 in this manner, the reduced portion 15 having the axial width (the gap width) decreasing in the radially outward direction is formed in the thrust bearing gap

C between the dynamic pressure generating groove area P and the inclined plane 17. The radially outermost portion corresponds to the minimum width portion Wmin of the thrust bearing gap C. Since the peripheral speed of the minimum width portion becomes the highest in the thrust bearing gap C during the rotation of the shaft member 2, the pumping power generated in the dynamic pressure generating groove area P becomes high as described above so that an enough dynamic pressure action can be obtained even at low rotational speed. As a result, the contact start rotational speed of the bearing device 1 can be kept low so that the wear of the thrust bearing portion T1 due to sliding contact between the end face 2b1 of the flange portion 2b and the upper end face 7c1 of the thrust plate 7c can be prevented. Therefore, high durability can be ensured even in uses where the operation of the motor is frequently started and stopped.

[0030]

Herein, the contact start rotational speed is such a rotational speed that the end face 2b1 of the flange portion 2b and the face 7c1 opposing thereto come into contact with each other at a speed lower than it, whereas the surfaces 2b1 and 7c1 do not come into contact with each other at a speed higher than it. Since contact time between the surfaces 2b1 and 7c1 immediately after the start or immediately before the stop of the operation of the motor is reduced if the contact start rotation speed is lowered, the wear of the thrust bearing portion T1 can be prevented.

[0031]

Although Fig. 1 illustrates the case where the dynamic pressure generating groove area P is formed on the upper end face 7c1 of the thrust plate 7c, the same effects can be obtained in the case where the dynamic pressure generating groove area P is formed on the lower end face of the flange portion 2b by forming inclined plane 24 on the lower end face 2b1.

[0032]

A method of forming the inclined plane 17 is arbitrary. Besides the formation by post-processing such as polishing, the



inclined plane 17 can also be formed simultaneously with injection molding of the resin part such as the flange portion 2b or the inner shaft portion 22 by providing an inclined part corresponding to the shape of the inclined plane on a mold surface of a mold for forming the resin part.

[0033]

In particular, if a resin is provided as a core of the shaft portion 2a so as to be integral with the resin of the flange portion 2b as in the case of this embodiment, the lower end face 2b1 of the flange portion 2b has a larger axial thickness of the resin on the radially inner side than that on the radially outer side by the presence of the resin of the inner shaft portion 22. Therefore, a sink in the axial direction generated when the resin is hardened is large on the radially inner side of the lower end face 2b1 while being smaller on the radially outer side. Accordingly, the inclined plane 17 can be formed by making use of a difference in the amount of sink simultaneously with the resin hardening. Since the above-mentioned post-processing or processing of the mold surface is no more needed in this case, further reduction in cost can be achieved. Such effects can be obtained at least in the case where a thickness of the resin on the lower end face 2b1 on the radially inner side is larger than that on the radially outer side. Therefore, in addition to the case where the inner shaft portion 22 made of a resin is formed over the total length of the shaft portion 2a as in the illustrated example, the same effects can also be expected in the case where the inner shaft portion 22 is formed exclusively for a lower part of the shaft portion 2a.

[0034]

The enlarged view in Fig. 1 exemplifies the case where the lower end face 2b1 of the flange portion 2b is entirely formed as the inclined plane 17. However, the inclined plane 17 is only required to be formed at least on a part facing the thrust bearing gap (a part being opposed to the dynamic pressure generating groove area P) generating a dynamic pressure effect. Therefore, the remaining part may also be formed as, for example,

a flat surface without any inclination. Moreover, although the inclined plane 17 is formed to have a curved cross-sectional shape in this enlarged view, the inclined plane 17 may also be formed as a tapered surface having a straight cross section. The curved inclined plane 17 may not only be formed at a single curvature but also be formed as a composite curve having two or more curvatures.

[0035]

Furthermore, although Fig. 1 illustrates the case where the inclined plane 17 is provided on the lower end face 2b1 of the flange portion 2b, the same inclined plane may also be formed on the upper end face 2b2 constituting the upper thrust bearing portion T2 so that the thrust bearing gap has a decreasing axial width in the radially outward direction. The inclined planes can also be formed both on the lower end face 2b1 and the upper end face 2b2 of the flange portion 2b.

[0036]

In order to confirm the above-described effects, a theoretical calculation of the contact start rotational speed is performed for the dynamic bearing device according to the present invention and a comparative dynamic bearing device.

[0037]

The theoretical calculation is performed with reference to the following document: Jiasheng Zhu and Kyosuke Ono, 1999, "A Comparison Study on the Performance of Four Types of oil Lubricated Hydrodynamic Thrust Bearings for Hard Disk Spindles", Transactions of the ASME, Vol.121, JANUARY 1999, pp. 114-120.

[0038]

The calculation conditions (a DF method and Sommerfeld boundary conditions) used in the theoretical calculation are as follows.

[0039]

Weight of rotary part W	6.5 g
Outer diameter of thrust bearing portion Do	6.5 mm
Inner diameter of thrust bearing portion Di	2.5 mm
Groove depth ho	7 $\mu$ m

Number of grooves $k$	16
Groove angle $\alpha$	30 degrees
Hill/groove ratio $\gamma$	1
Lubricating oil viscosity $\eta$	5.97 mPa · S

The minimum width  $W_{min}$  of the thrust bearing gap is set

to 0.05  $\mu\text{m}$ .

[0040]

According to the result of the theoretical calculation based on the above-described conditions, it is found that the contact start rotational speed becomes lower as the angle  $\theta$  of the inclined plane 24 becomes smaller. Furthermore, it is found that the contact start rotational speed is remarkably increased if the  $\theta$  exceeds  $0.6^\circ$ . Therefore, it is desirable that the angle  $\theta$  of the inclined plane 24 is  $0.6^\circ$  or less, more desirably,  $0.3^\circ$  or less.

[0041]

The application of the present invention is not limited to the dynamic bearing device 1 having the thrust bearing portion T1 between the lower end face 2b1 of the flange portion 2b and the bottom portion 7c of the housing 7; the present invention can be widely applied to dynamic bearing devices including a thrust bearing portion constituted by a dynamic pressure bearing in general. For example, the present invention is similarly applicable to the following dynamic bearing device (not shown). One of the thrust bearing surface 11a and the thrust receiving surface 11b of the thrust bearing portion is formed on the end of the housing 7 on the opening side, while the other is formed on an end face of a rotary member (for example, the disk hub 3) being opposed thereto.

[0042]

The case where the dynamic pressure bearing including the dynamic pressure generating grooves is used as each of the radial bearing portions R1 and R2 has been described above. However, any bearing can be used as the radial bearing portions R1 and R2 as long as it supports the shaft member 2 in the radial direction in a non-contact manner by an oil film of the

lubricating oil, formed in the radial bearing gap. For example, in addition to a bearing including an area serving as the radial bearing surface being composed of a plurality of circles (a circular bearing) and a step bearing, a bearing including an area having a perfect circular cross section without any dynamic pressure generating grooves as the radial bearing surface (a cylindrical bearing) can also be used.

[Brief Description of Drawings]

[0043]

[Fig. 1] Fig. 1 shows a cross-sectional view of a shaft member and an enlarged view of a principal part thereof using a dynamic pressure bearing device according to the present invention;

[Fig. 2] Fig. 2 is a cross-sectional view of a spindle motor using the dynamic pressure bearing device;

[Fig. 3] Fig. 3 is a cross-sectional view of the dynamic pressure bearing device;

[Fig. 4] Fig. 4 is a plan view of a inner bottom surface of a thrust plate.

[Description of Reference Characters]

[0044]

- 1 dynamic pressure bearing device
- 2 shaft member
- 2a shaft portion
- 2b flange portion
- 2b1 lower end face
- 2b2 upper end face
- 3 disc hub
- 4 stator coil
- 5 rotor magnet
- 7 housing
- 7c bottom portion (thrust plate)
- 7c1 upper end face (opposed face)
- 8 bearing sleeve
- 8a inner peripheral face
- 8c end face
- 10 seal member

10a inner peripheral face  
21 inner shaft portion  
22 outer shaft portion  
24 inclined plane  
C thrust bearing gap  
P dynamic pressure generating groove area  
R1 first radial bearing portion  
R2 second radial bearing portion  
T1 first thrust bearing portion  
T2 second thrust bearing portion  
 $\theta$  angle  $\theta$  of inclination

[Name of document] Written abstract

[Object] The present invention has an object of improving wear resistance of a thrust bearing portion.

[Constitution] A flange portion 2b of a shaft member 2 is formed of resin, and pressure is generated by the dynamic pressure effect of a fluid in the thrust bearing gap between its end surface 2b1 and inner bottom surface 7c1 of the housing 7, and the shaft member 2 is supported in a non-contact manner in the thrust direction by this pressure. An inclined plane 24 coming closer to the inner bottom surface 7c1 in a radially outward direction, is formed in a part facing the thrust bearing gap C of the end face 2b1 of the flange portion 2b.

[Representative Drawing] Fig. 1